PCA Off-Road Driving Tour Self-Inspection Safety Checklist

Effective 2020

The following items must be checked and verified by the driver prior to arriving at the staging area for all PCA off-road driving tours, then this form shall be submitted to the tour leader. **Note: there is no intention that vehicle parts or components be removed in order to perform this inspection.** The vehicle is expected to be safe to drive on the specified off-road route. The owner of the vehicle for this off-road driving tour understands completion of this checklist does not guarantee there will be no damage to his or her vehicle during this off-road event.

☐ Check overall tire condition, including spare tire, for typical wear, with no bulges, gashes or flat spots.

	Check all tire pressures comply with manufacturer's recommended values.
	Visually check condition of vehicle undercarriage. There should be nothing loose or hanging.
	Visually check under the vehicle for fluid leaks – brake lines especially.
	From exterior of vehicle, visually check brake pads and rotors are in good condition. No brake pad
	warning lights on instrument displays.
	Check fluid levels are above the minimum level required (oil, coolant, brakes, power steering,
	transmission, windshield wiper fluid).
	Check condition of all visible hoses, clamps and belts in the engine compartment. There should be no
	leaks and/or deterioration.
	Check overall condition of vehicle exterior. No loose equipment.
	Check tow hook is readily accessible within the vehicle.
	Check interior of vehicle. No unsecured items, including in the rear cargo/storage area of the vehicle.
	Check auto insurance is current, and the insurance card and vehicle registration are in the vehicle.
	Check vehicle has sufficient fuel for the route.
	Additional house for CATECORY 2 Off Road Driving Towns
	Additional Items for CATEGORY 3 Off-Road Driving Tours
	, , , , , , , , , , , , , , , , , , ,
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value.
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value.
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through.
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts.
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp or heavy blanket, a tire plug kit, an air compressor and two-way radios are secured in the vehicle.
	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp or heavy blanket, a tire plug kit, an air compressor and two-way radios are secured in the vehicle.
Printe	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp or heavy blanket, a tire plug kit, an air compressor and two-way radios are secured in the vehicle. Lead or sweep vehicles make sure a shovel and a bottle jack are secured in the vehicle.
Printe	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp or heavy blanket, a tire plug kit, an air compressor and two-way radios are secured in the vehicle. Lead or sweep vehicles make sure a shovel and a bottle jack are secured in the vehicle.
Printe	Check condition of all wheels for no visible damage. Check all lug nuts/bolts are installed and torqued to their recommended value. Check the exhaust system integrity. Nothing loose, nothing rusted through. If battery is accessible without requiring removal of other components, check it is securely attached and cables are secure on the battery posts. If you will be a lead vehicle, make sure a 20,000lb-rated tow strap/cable (not rope) with hooks, a tarp or heavy blanket, a tire plug kit, an air compressor and two-way radios are secured in the vehicle. Lead or sweep vehicles make sure a shovel and a bottle jack are secured in the vehicle.